

S4200-SI Series L2 Gigabit Access Switch

Product Overview

DCN S4200-SI series are cost-effective GbE standalone switches which provide enterprise-class access for campus and branch applications. These fully managed switches can provide advanced Layer 2 features as well as optional Power over Ethernet Plus (PoE+) power. Designed for operational simplicity to lower total cost of network, S4200 Series provide scalable, secure, and energy-efficient business network access with intelligent services.

Appearance	Description
 S4200-10P-SI(R2)	● 8x10/100/1000Base-T+2x100/1000Base-X (SFP) ● 1 console ● AC power supply ● Switching capacity: 20Gbps ● Forwarding rate: 14.88Mpps
 S4200-10P-P-SI(R2)	● 8x10/100/1000Base-T+2x100/1000Base-X (SFP) ● 1 console ● PoE+, up to 125w ● AC power supply ● Switching capacity: 20Gbps ● Forwarding rate: 14.88Mpps
 S4200-28P-SI(R3)	● 24x10/100/1000Base-T+4x100/1000Base-X (SFP) ● 1 console ● AC power supply ● Switching capacity: 56Gbps ● Forwarding rate: 41.7Mpps
 S4200-28P-P-SI(R2)	● 24x10/100/1000Base-T+4x100/1000Base-X (SFP) ● 1 console ● PoE+, up to 375w ● AC power supply ● Switching capacity: 56Gbps ● Forwarding rate: 41.7Mpps

Key Features and Highlights

Green Energy

S4200-SI series complies with **IEEE 802.3az** (Energy-Efficient Ethernet) standard, dramatically lower power consumption

With the **Innovative port-LED Shut-off** function, the user can automatically set the switch port-LED UP or DOWN at a specified period according to their needs to achieve functional, energy-saving correct results.

A full account of low noise requirements of the environment, S4200-SI uses **Fanless Design and Smart fan** strategies to real-time temperature monitoring system, and reduce the noise pollution.

Simple Operation and Maintenance

VCT, DDM (Digital Diagnostic Monitoring) and other features achieve rapid detection of the network failures; reduce operation and maintenance difficulty.

High Reliability

S4200-SI series support 4 Gigabit uplink ports, which could be designed to offer redundant uplinks with

various ring protection applications, effectively raised the expansibility and performance of network.

G.8032 provides sub-50ms protection and recovery switching for Ethernet traffic in a carrier ring topology. S4200-SI series support G.8032 v2 and can be deployed in a variety of complex network topologies including single ring, tangent ring, intersecting rings, double rings and other home networking

Abundant Multicast Features

S4200-SI series also support **MVR** (Multicast VLAN Register), selectively allows traffic to cross between different VLANs for bandwidth and security reasons. With MVR Trunk function, which could associate multicast VLAN to trunk port, S4200-SI series combines the VLAN data into the same link, saving lots of resources for users.

S4200-SI series could prevent multicast traffic from flooding via IGMP Snooping, while multicast traffic is only forwarded to ports associated to multicast devices.


Product Specifications

Item	S4200-10P-SI(R2)	S4200-10P-P-SI(R2)	S4200-28P-SI(R3)	S4200-28P-P-SI(R2)
Ports	8 x 100/1000Base-T + 2 x 100/1000Base-X (SFP) Auto-MIDX	8 x 100/1000Base-T + 2 x 100/1000Base-X (SFP) Auto-MIDX	24 x 100/1000Base-T + 4 x 100/1000Base-X (SFP) Auto-MIDX	24 x 100/1000Base-T + 4 x 100/1000Base-X (SFP) Auto-MIDX
	Performance			
Switching Capacity	20Gbps	20Gbps	56Gbps	56Gbps
Forwarding Rate	14.88Mpps	14.88Mpps	41.7Mpps	41.7Mpps
Flash	32M	32M	32M	32M
RAM	128M	128M	256M	256M
MAC ADDRESS	8K			
Jumbo Frame	10K			
ACL Table	1408			
Queues per port	8			
VLAN TABLE	4K			
	Physical Features			
Dimension(W*H*D)	265mm*44mm*160m m	330mm*44mm*220m m	440mm*44mm*170m m	440mm*44mm*260m m
Power Input	100~240VAC, 50~60Hz			
Power Consumption	7w	145w	20w	440w
Cooling	Passive	Passive	Passive	Active
Temperature	Working 0℃~50℃, Storage -40℃~70℃			
Relative Humidity	5%~95%, non-condensing			
EMC Safety	CE, RoHS			
	Main Features			
Forwarding	Storage and Forwarding			

Item		S4200-10P-SI(R2)	S4200-10P-P-SI(R2)	S4200-28P-SI(R3)	S4200-28P-P-SI(R2)
VLAN		Port-based VLAN, IEEE802.1Q, private VLAN, Protocol VLAN, Voice VLAN, MAC VLAN Normal QinQ, Selective QinQ, Flexible QinQ VLAN Translation, N:1 VLAN Translation			
DHCP		IPv4/IPv6 DHCP Client, IPv4/IPv6 DHCP Relay Option 82, Option 37/38 IPv4/IPv6 DHCP Snooping, IPv4/IPv6 DHCP Server			
Reliability	Spanning Tree	802.1D STP, 802.1W RSTP, 802.1S MSTP Root Guard, BPDU Guard, BPDU Forwarding			
	LACP	8 groups / 8 ports			
	L2 Ring Protection	MRPP ERPS(G.8032) Loopback Detection Fast Link			
Security		IP ACL, MAC ACL, MAC-IP ACL, User-Defined ACL Time Range ACL ACL rules can be configured to port, VLAN Storm Control based on packets and bytes Port Security, MAC Limit based on VLAN and Port Anti-ARP-Spoofing , Anti-ARP-Scan, ARP Binding ND Snooping IP Source Guard, Dynamic ARP Inspection IEEE 802.1x Authentication, Authorization, Accounting Radius, TACACS+			
Multicast		IGMP v1/v2/v3 snooping, IGMP Fast leave MVR MLD v1/v2 snooping IPv4/IPv6 DCSCM			
QoS		8 Queues Per Port Bandwidth Control Flow Redirect Classification based on ACL, VLAN ID, COS, TOS, DSCP Policing Based on Port and VLAN Single Rate single barrel double color for Policing Remark DSCP, COS/802.1p, Precedence, TOS SP, WRR, SWRR, DWRR for Scheduling Match the IP fragmentation of message			
Maintenance Operation Management		TFTP/FTP CLI, Telnet, Console Web/SSL (IPv4/IPv6) SSH (IPv4/IPv6) SNMPv1/v2c/v3 SNMP Trap Public & Private MIB interface RMON 1, 2, 3, 9 Ping Syslog (IPv4/IPv6) SNTP/NTP (IPv4/IPv6) Multiple Configuration Files Port Mirror, CPU Mirror, RSPAN VCT, DDM ULDP(like Cisco UDLD) LLDP/LLDP MED			
Green Energy		IEEE 802.3az (Energy Efficient Ethernet) Fanless (10P, 10P-PL & 28P) LED Shut-off			

Typical Application

Gigabit access in SMB network



Order Information

Product	Description
S4200-10P-SI(R2)	L2 Gigabit Intelligent Ethernet Switch with 8*10/100/1000Base-T and 2*100/1000Base-SFP ports, 100-240VAC Power Input
S4200-10P-P-SI(R2)	L2 Gigabit Intelligent Ethernet PoE Switch with 8*10/100/1000Base-T and 2*100/1000Base-SFP ports, 100-240VAC Power Input. 30w POE+ Supported. PoE output 125W
S4200-28P-SI(R3)	L2 Gigabit Intelligent Ethernet Switch with 24*10/100/1000Base-T and 4*100/1000Base-SFP ports, 100-240VAC Power Input
S4200-28P-P-SI(R2)	L2 Gigabit Intelligent Ethernet PoE Switch with 24*10/100/1000Base-T and 4*100/1000Base-SFP ports, 100-240VAC Power Input. 30w POE+ Supported. PoE output 375W